

Milliken Infrastructure

# RenewWrap™

## Primer/Steel (FP-WE7)

Low-Viscosity Primer for Steel and Concrete Substrates



BRIDGES + ROADWAYS



BUILDINGS + PARKING FACILITIES



OIL, GAS + INDUSTRIAL



**RenewWrap™ Primer/Steel (FP-WE7)** is a 2-part, 100% solids, epoxy adhesive used to prime surfaces of steel or concrete substrates prior to applying the RenewWrap™ Strand Sheet® reinforcement. RenewWrap™ Primer/Steel (FP-WE7) is supplied in two-part kits.

### Benefits

- Can be used on both steel and concrete substrates
- Applied using a medium nap paint roller
- VOC compliant, low odor
- 100% solvent free

### Typical Uses

The RenewWrap Strand Sheet Strengthening system may be used to strengthen or retrofit a wide range of concrete and steel structural members including columns, beams, slabs, walls, pipes, tunnels, deck, piers, piles, etc.

- Do not thin with solvents
- Extend fatigue life of steel structures
- Restore strength of corrosion-deteriorated steel structures.
- Strengthen for load increases
- Address changes in structural system, like slab openings
- Retrofit for seismic, wind, or blast
- Restore strength to damaged members like fire or vehicle impact
- Restore strength to deteriorated members subject to corrosion
- Strengthen for design/construction errors

### Limitations

- Substrate /ambient temperature must be greater than 40 °F (4 °C)
- Do not thin with solvents

*Strand Sheet® products are based on technology developed by Nippon Steel & Sumkin Materials Company, Ltd.*

*Strand Sheet® is a registered trademark of Nippon Steel & Sumkin Materials Co.*

### Storage & Shelf Life

Store in a cool, dry place at 40-90 °F (4-32 °C) away from flame or other hazards.

Shelf life is 12 months when properly stored in unopened containers.

### Caution

Consult Safety Data Sheets (SDS) and always use appropriate personal protective equipment when handling resins.

### Alternate Product Designation

FP-WE7

Milliken Infrastructure


# RenewWrap™

## Primer/Steel (FP-WE7)

Low-Viscosity Primer for Steel and Concrete Substrates

 BRIDGES + ROADWAYS

 BUILDINGS + PARKING FACILITIES

 OIL, GAS + INDUSTRIAL

### Physical Properties

PROPERTY	VALUE	TEST METHOD
Mix Ratio	2:1 (by weight)	
Specific Gravity	1.20 (mixed)	
Glass Transition Temperature	125 °F (52 °C)	ASTM D3418

### Field Characteristics

PROPERTY	VALUE
Pot Life	90 minutes @ 77 °F (25 °C)

### Packaging

COMPONENT	QUANTITY	PACKAGE
Part A	14.7 lbs (6.67 kg)	Steel cans
Part B	7.3 lbs (3.33 kg)	Steel cans
Unit Sizes	22 lbs (10 kg) 2.20-gallon kit	

### Coverage Rates/Ply

SUBSTRATE	COVERAGE RATE (BY WEIGHT)	COVERAGE RATE (BY VOLUME)
Steel	0.20 kg/m <sup>2</sup>	250 SF/gallon
Concrete <sup>1</sup>	0.25 kg/m <sup>2</sup>	200 SF/gallon

#### NOTES:

1. RenewWrap™ Primer/Steel (FP-WE7) may also be used to prime concrete substrates when installing RenewWrap CF300/HM ultra-high modulus FRP strengthening fabrics.

Before using any Milliken Infrastructure Solutions, LLC product, the user must review the most recent version of the product's technical data sheet, material safety data sheet and other applicable documents, available at [www.strengtheningsolutions.milliken.com](http://www.strengtheningsolutions.milliken.com) or by calling 1-855-655-6750. LIMITED WARRANTY: Milliken Infrastructure Solutions, LLC is very proud of our innovative RenewWrap™ products (the "Products") and our superior customer service. We hereby warrant to the original purchaser that the Products meet Milliken's standard specifications at the time of delivery from us. If the Products are found to be defective because they do not meet this Warranty, then we will as the sole remedy either (at our option) refund the purchase price for those Products or provide replacement Products (in either case, not including shipping, installation or any other cost). Naturally, we are not responsible or liable for degradation, damage, liability or defect in, or related to, the Products caused by improper storage, use, installation or maintenance, any other party's representations, warranties, actions, or omissions, or acts of God. WE MAKE NO REPRESENTATION OR WARRANTY BEYOND THE EXPLICIT STATEMENTS CONTAINED IN THIS WARRANTY AND ALL OTHER EXPRESS AND IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, INFRINGEMENT, OR ANY WARRANTIES BASED UPON SAMPLES, MODELS, OR SPECIFICATIONS, ARE HEREBY EXPRESSLY DISCLAIMED. NOTWITHSTANDING ANYTHING TO THE CONTRARY, IN NO EVENT SHALL WE BE LIABLE TO THE ORIGINAL PURCHASER OR ANYONE ELSE FOR ANY CONSEQUENTIAL, INDIRECT, SPECIAL, OR EXEMPLARY (OR ANY SIMILAR TYPE OF) DAMAGES RELATED TO THE PRODUCTS. As each customer's use of our Products and situation may be different, information we provide, including without limitation, use or installation suggestions, test results, samples, etc. is provided in good faith but without warranty and without accepting any responsibility or liability. Each customer must test and be responsible for its own specific use, installation, application, etc. All sales are exclusively subject to our standard terms of sale posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing. This Warranty is governed by the laws of the United States and the State of South Carolina, U.S.A. (without giving effect to its conflict of law principles), and any party desiring to take action under this Warranty hereby submits to the exclusive jurisdiction of the courts in such jurisdiction and waive any inconvenient forum claims related thereto. In the unlikely event that you have a warranty issue, please contact your distributor or sales representative to discuss and resolve the matter in accordance with this Warranty.

[infrastructure.milliken.com](http://infrastructure.milliken.com)  
855-655-6750

MILLIKEN INFRASTRUCTURE   
A *Milliken* COMPANY

FRP1085-1217